AUTOVIEW 3100/3200 DIGITAL KVM SWITCHES

SECURE ACCESS FROM ANY LOCATION

Secure remote and local access in a single solution for the SMB environment

The Avocent AutoView® 3100 and AutoView 3200 digital KVM switching systems include access for one or two digital users and access for a local user. The on-board Web interface provides secure, remote access to target devices from any location.

With this all-in-one SMB solution, you can remotely manage all connected servers and serial-based devices from your desk or across town. The local port gives you convenient at-the-rack access. Both solutions let you manage multi-platform target devices and include local PS/2 and USB peripheral support.

The convenience of CAT 5 cabling will dramatically reduce cable clutter and cost for your SMB server rooms.

The AutoView 3100 and AutoView 3200 digital KVM switches offer encrypted SSL-128bit, DES, 3DES or AES communication, which are superior to industry standards. Other security features include 64 user accounts and an access control list for each user.

The AutoView 3100 and AutoView 3200 digital KVM switching systems provide secure access for one or two digital users and a local analog user in a single solution.

BENEFITS

- **Security.** Encrypted IP communication between the user's browser and switch can be SSL-128bit, DES, 3DES or AES.
- **On-board Web Interface.** No need to load and manage another software program on the users PC.
- **Access.** One or two digital paths let you remotely manage all connected servers and serial-based devices. A local port provides at-the-rack access for a local analog user.
- **Multi-platform Support.** Local PS/2 and USB connections and multi-platform target devices, including PS/2, USB, Sun and serial support.
- **CAT 5 Cabling.** Slim, CAT 5-designed, integrated access cables for PS/2 or USB connectivity.

AUTOVIEW 3100/3200 DIGITAL SWITCHES SPECIFICATIONS

MECHANICAL

- **Height** - 1.72 in. (4.37 cm)
- **Depth** - 10.98 in. (27.98 cm)
- **Width** - 17 in. (43.18 cm)
- **Weight** - 7.3 lbs. (3.31 kg) without cables
- **Style** - Rack mount

ENVIRONMENTAL / POWER / HARDWARE

- **Operating Temperature** - 32° (0°C) to 104° (40°C)
- **Storage** - -4° (-20°C) to 158° (70°C)
- **Operating Voltage** - 100 - 240 VAC
- **Power Frequency** - 50 - 60 Hz autosensing
- **Input** - 40W maximum
- **Computer** - PS/2, Sun and USB
- **Video Modes** - VGA, SVGA (XGA, XGA-II with adapter),
  Local port maximum: 1600x1200 @ 75Hz
  Remote port maximum: 1280x1024 @ 75Hz
- **Peripherals** - USB keyboard and mouse, PS/2 keyboard, PS/2 mouse, IntelliMouse

ORDERING DETAILS

- **Digital KVM Switches**
  AV3100-001 AutoView 3100 digital KVM switch, one digital path with local port
  AV3200-001 AutoView 3200 digital KVM switch, two digital paths with local port
- **Cables**
  PS2IAC-7 7ft PS/2 CAT 5 integrated access cable
  PS2IAC-10 10ft PS/2 CAT 5 integrated access cable
  PS2IAC-15 15ft PS/2 CAT 5 integrated access cable
  USBIAC-7 7ft USB CAT 5 integrated access cable
  USBIAC-10 10ft USB CAT 5 integrated access cable
  USBIAC-15 15ft USB CAT 5 integrated access cable
  AVRIQ-PS2 PS/2 server interface module
  AVRIQ-USB USB server interface module
  AVRIQ-SRL Serial interface module (extended version)
  AVRIQ-VSN Sun server interface module

STANDARDS

- **Approved Agency**
  UL, FCC, cUL, ICES-003, CE, GS, VCCI, MIC, C-Tick, GOST.

WARRANTY

- **Two Year**

The AutoView 3100/3200 digital KVM switches let you securely and conveniently access devices from any location.



Avocent
The Power of Being There.

Corporate Headquarters
4991 Corporate Drive, Huntsville, AL 35805
TEL 866.277.1924 FAX 256.430.4030
www.avocent.com

Avocent, the Avocent logo, The Power of Being There and AutoView are registered trademarks of Avocent Corporation or its affiliates. All other marks are the property of their respective owners. Copyright © 2006. Avocent Corporation. All rights reserved.

0706-AV31003200-TP